

TYRES

Product group	Tyres
Item number	15785410
Valid tyre size	12.00 R 24
LI / SI / PR	158 B
TL/TT	TT
Brand	BKT
Tread pattern	Earthmax SR 44



Notes and features

- Excellent traction and driving comfort
- E-4 tyre with a *** -marking, approved up to 50 km/h
- Particularly heat and puncture resistant rubber compound
- Suitable for multi-purpose vehicles in the mining industry, dump trucks, transport vehicles, timber trucks etc.
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	15785410
EAN	8903094034284
Valid tyre size	12.00 R 24
Alternative size 1	325/95R24
LI / SI / PR	158 B
TL/TT	TT
Brand	BKT
Tread pattern	Earthmax SR 44
TRA Code	E4
Star Rating	***
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	97,14
Recommended rim size	8.50V
Permitted rim size	9.00V
Maximum air pressure [bar].	7,00
Section width (mm)	310
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	575
Rolling circumference [mm].	3790
Tread depth (mm)	31,0
Tyre capacity 75% [litr.]	123
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 B	4250	50		7,00	