

TYRES

Product group	Tyres	
Item number	15785411	
Valid tyre size	325 / 95 R 24	
LI / SI / PR	158 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Earthmax SR 44	



Notes and features

- Excellent traction and driving comfort
- E-4 tyre with a *** -marking, approved up to 50 km/h
- Particularly heat and puncture resistant rubber compound
- Suitable for multi-purpose vehicles in the mining industry, dump trucks, transport vehicles, timber trucks etc.
- Important: Mounting only permitted on multi-part rim.



Technical Informations

Maria according	45705.444
Item number	15785411
EAN	8903094054282
Valid tyre size	325 / 95 R 24
Alternative size 1	12.00R24
LI / SI / PR	158 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 44
TRA Code	E4
Star Rating	***
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	97,74
Recommended rim size	8.50V
Maximum air pressure [bar].	7,00
Section width (mm)	310
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	575
Rolling circumference [mm].	3790
Tread depth (mm)	30,5
E-Ready	No

Load capacity

ı	ndex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
1	158 B	4250	50		7,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.