

TYRES

Product group	Tyres
Item number	15785415
Valid tyre size	15.5 R 25
LI / SI / PR	169 A2 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 30



Notes and features

- Full steel casing with extra steel belt layers for outstanding stability and puncture resistance
- Non-directional tread pattern for excellent traction properties
- The running surface's special rubber compound provides for optimum protection from cutting and impact damage as well as from heat development in the tyre during transport journeys
- Ideal for earthmovers, tippers and graders
- Suitable for mounting on one-piece rim

Technical Informations

Item number	15785415
EAN	8903094052158
Valid tyre size	15.5 R 25
LI / SI / PR	169 A2 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 30
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	125,09
Recommended rim size	12.00/1.3
Maximum air pressure [bar].	5,25
Section width (mm)	397
Outer diameter of tyre [mm].	1276
Stat. radius (SLR) [mm]	574
Rolling circumference [mm].	3809
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A2	5800	10	Loader dozer	5,25	
160 B	4500	50	Transport	5,25	