

TYRES

Product group	Tyres
Item number	15785416
Valid tyre size	15.5 R 25
LI / SI / PR	146 A8 / 169 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22



Bohnenkamp
Moving Professionals



Notes and features

- The BKT Earthmax SR 22 is an EM radial tyre for wheel loaders in winter use on snowy and icy surfaces
- The all-steel construction provides particular durability
- The block pattern with its large contact area provides good traction and stability

Technical Informations

Item number	15785416
EAN	8903094063758
Valid tyre size	15.5 R 25
LI / SI / PR	146 A8 / 169 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22
TRA Code	G2/L2
Star Rating	*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	124,32
Recommended rim size	12.00/1.3
Permitted rim size	12.00/1.3DC
Maximum air pressure [bar].	6,50
Section width (mm)	385
Outer diameter of tyre [mm].	1275
Stat. radius (SLR) [mm]	557
Rolling circumference [mm].	3841
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A8	3000	40	Grader	3,00	
169 A2	5800	10	Loader dozer	5,00	