

TYRES

Product group	Tyres
Item number	15785417
Valid tyre size	15.5 R 25
LI / SI / PR	169 A2 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 313



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 313 is a newly-developed EM radial tyre for use on articulated dump trucks and wheel loaders
- Its cut-resistant rubber compound and the closed tread pattern design protect the tyre from damages when working on rocky surfaces
- The square tyre shoulder provides good ground contact and excellent steering characteristics
- The all-steel radial casing design with multi-layer steel belts guarantees a long service life
- The tyre is ideally suited for haulage and loading operations

Technical Informations

Item number	15785417
EAN	8903094066964
Valid tyre size	15.5 R 25
LI / SI / PR	169 A2 / 160 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 313
TRA Code	L3/E3
Star Rating	*/**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	126,58
Recommended rim size	12.00/1.3
Maximum air pressure [bar].	5,25
Section width (mm)	394
Outer diameter of tyre [mm].	1265
Stat. radius (SLR) [mm]	566
Rolling circumference [mm].	3822
Tread depth (mm)	26,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A2	5800	10	Loader dozer	5,00	
160 B	4500	50	Transport	5,25	