

TYRES

Product group	Tyres	
Item number	15785420	
Valid tyre size	16.00 R 25	
LI / SI / PR	200 A5	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Portmax PM 93 Plus	



Notes and features

- The Portmax PM 93 Plus was specially developed for straddle carriers.
- Its strong, all-steel casing provides excellent durability and ride comfort.
- The special rubber compound ensures a long service life.
- The unique tread pattern design reduces rolling resistance which results in lower fuel consumption.
- Attention: mounting on multi-piece rim only.



Technical Informations

Item number	15785420
EAN	8903094047680
Valid tyre size	16.00 R 25
LI / SI / PR	200 A5
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PM 93 Plus
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	293,19
Recommended rim size	11.25/2.0
Permitted rim size	11.25/2.0IF
Maximum air pressure [bar].	10,00
Section width (mm)	425
Outer diameter of tyre [mm].	1515
Stat. radius (SLR) [mm]	699
Rolling circumference [mm].	4582
Tread depth (mm)	49,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
200 A5	14000	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.