

## TYRES

Product group	Tyres
Item number	15785435
Valid tyre size	17.5 R 25
LI / SI / PR	176 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 51



## Notes and features

- Reinforced, resistant all-steel carcass.
- Non-directional tyre, developed for wheel loaders and wheel dozers.
- Optimal lug angles for excellent traction in loading operations, grading work or moving larger quantities in the earthmoving sector.
- Extra deep tread (L5) combined with a robust and cut-resistant rubber compound guarantees a long service life.
- Developed for normal to extremely tough use.
- Self-cleaning tread pattern.
- Important: Assembly only permitted on multi-piece wheel.

**Technical Informations**

Item number	15785435
EAN	8903094046249
Valid tyre size	17.5 R 25
LI / SI / PR	176 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 51
TRA Code	L5
Star Rating	*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	256,67
Recommended rim size	14.00/1.5
Permitted rim size	13.00LR/1.4, 14.00LR/1.5, 14.00/1.5(DC), 14.00/1.3(DC)
Maximum air pressure [bar].	5,00
Section width (mm)	437
Outer diameter of tyre [mm].	1398
Stat. radius (SLR) [mm]	630
Rolling circumference [mm].	4110
Tread depth (mm)	61,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 A2	7100	10	Loader dozer	5,00	
	5965	20	Loader dozer	5,00	