

TYRES

Product group	Tyres
Item number	15785436
Valid tyre size	17.5 R 25
LI / SI / PR	167 B / 182 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22



Bohnenkamp
Moving Professionals



Notes and features

- The BKT Earthmax SR 22 is an EM radial tyre for wheel loaders in winter use on snowy and icy surfaces
- The all-steel construction provides particular durability
- The block pattern with its large contact area provides good traction and stability

Technical Informations

Item number	15785436
EAN	8903094052387
Valid tyre size	17.5 R 25
LI / SI / PR	167 B / 182 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22
TRA Code	E2/L2
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	162,32
Recommended rim size	14.00/1.5
Permitted rim size	14.00/1.5(DC), 14.00/1.3(DC)
Maximum air pressure [bar].	6,50
Section width (mm)	452
Outer diameter of tyre [mm].	1350
Stat. radius (SLR) [mm]	590
Rolling circumference [mm].	3950
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 B	5450	50		5,25	
182 A2	8500	10		6,50	