

## **TYRES**

Product group	Tyres
Item number	15785442
Valid tyre size	18.00 R 25
LI / SI / PR	207 A5 (214 A5)
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PM 90



## **Notes and features**

- The BKT Portmax PM 90 was specially developed for container handling equipment like reach stackers.
- Its optimum contact area enables even weight distribution.
- Thanks to its strong casing and reinforced sidewalls, the tyre provides excellent stability in lift mode.
- The deep tread pattern with the wide, centre rib and the wear-resistant tread compound ensure the tyre's long service life.
- Its optimal lug angle with reinforced shoulders minimises tyre damage.
- The tyre is able to dissipate static charge from the vehicle.



## **Technical Informations**

Item number	15785442
EAN	8903094045662
Valid tyre size	18.00 R 25
LI / SI / PR	207 A5 (214 A5)
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PM 90
Star Rating	***
Carcass properties	All-Steel
Antistatic	Yes
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	425,79
Recommended rim size	13.00/2.5
Maximum air pressure [bar].	10,00
Section width (mm)	495
Outer diameter of tyre [mm].	1655
Stat. radius (SLR) [mm]	730
Rolling circumference [mm].	5024
Tread depth (mm)	63,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
207 A5	17500	25		10,00	
214 A5	21200	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.