

TYRES

Product group	Tyres
Item number	15785450
Valid tyre size	20.5 R 25
LI / SI / PR	186 A2 / 177 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 30



Notes and features

- Full steel casing with extra steel belt layers for outstanding stability and puncture resistance
- Non-directional tread pattern for excellent traction properties
- The running surface's special rubber compound provides for optimum protection from cutting and impact damage as well as from heat development in the tyre during transport journeys
- Ideal for earthmovers, tippers and graders
- Suitable for mounting on one-piece rim

Technical Informations

Item number	15785450
EAN	8903094027729
Valid tyre size	20.5 R 25
LI / SI / PR	186 A2 / 177 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 30
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	237,26
Recommended rim size	17.00/2.0
Permitted rim size	17.00/1.7, 17.00/2.0IF
Maximum air pressure [bar].	5,25
Section width (mm)	529
Outer diameter of tyre [mm].	1487
Stat. radius (SLR) [mm]	663
Rolling circumference [mm].	4439
Tread depth (mm)	32,0
Tyre capacity 75% [litr.]	345
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
186 A2	9500	10	Loader dozer	5,00	
177 B	7300	50	Transport	5,25	