

## TYRES

Product group	Tyres
Item number	15785455
Valid tyre size	20.5 R 25
LI / SI / PR	186 A2 / 177 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 31



## Notes and features

- Earthmax SR 31 is a radial all steel tyre for use on earthmovers, dozers and articulated joint tippers
- The construction featuring multiple layers of steel belts provides for a unique degree of resistance and stability
- The non-directional tread pattern allows for first-rate traction and manoeuvrability even on muddy soil as well as high driving comfort
- The particularly cut and heat resistant running surface compound provides for a tyre with a long service life
- The reduced rolling resistance results in significant fuel savings

## Technical Informations

Item number	15785455
EAN	8903094060610
Valid tyre size	20.5 R 25
LI / SI / PR	186 A2 / 177 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 31
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	237,26
Recommended rim size	17.00/2.0
Maximum air pressure [bar].	5,25
Section width (mm)	540
Outer diameter of tyre [mm].	1480
Stat. radius (SLR) [mm]	663
Rolling circumference [mm].	4449
Tread depth (mm)	32,0
Tyre capacity 75% [ltr.]	345
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
186 A2	9500	10	Loader dozer	5,00	
177 B	7300	50	Transport	5,25	