

TYRES

Product group	Tyres
Item number	15785502
Valid tyre size	23.5 R 25
LI / SI / PR	195 A2 / 185 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 31



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Earthmax SR 31 is a radial all steel tyre for use on earthmovers, dozers and articulated joint tippers
- The construction featuring multiple layers of steel belts provides for a unique degree of resistance and stability
- The non-directional tread pattern allows for first-rate traction and manoeuvrability even on muddy soil as well as high driving comfort
- The particularly cut and heat resistant running surface compound provides for a tyre with a long service life
- The reduced rolling resistance results in significant fuel savings

Technical Informations

Item number	15785502
EAN	8903094048434
Valid tyre size	23.5 R 25
LI / SI / PR	195 A2 / 185 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 31
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	340,52
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	5,00
Section width (mm)	612
Outer diameter of tyre [mm].	1607
Stat. radius (SLR) [mm]	711
Rolling circumference [mm].	4797
Tread depth (mm)	35,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
195 A2	12150	10	Loader dozer	5,00	
185 B	9250	50	Transport	5,00	