

TYRES

Product group	Tyres
Item number	15785510
Valid tyre size	23.5 R 25
LI / SI / PR	195 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 53



Notes and features

- Hardwearing L5 tread pattern design developed for wheel loaders and wheeled bulldozers
- Excellent suitability e.g. in quarries or in the mining industry for face-working operations and work on stony, very rough ground.
- The closed tread pattern design and the high tread pattern ratio (250%) make the SR53 the best choice for use in recycling e.g. scrap yards.
- Extremely robust and cut resistant rubber compound with minor abrasion and a long service life
- Very good self-cleaning properties with stone ejection
- Important: Assembly only permitted on multi-piece wheel.

Technical Informations

Item number	15785510
EAN	8903094045839
Valid tyre size	23.5 R 25
LI / SI / PR	195 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 53
TRA Code	L5
Star Rating	*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	533,91
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	5,00
Section width (mm)	604
Outer diameter of tyre [mm].	1666
Stat. radius (SLR) [mm]	758
Rolling circumference [mm].	5015
Tread depth (mm)	84,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
195 A2	12150	10		5,00	