

TYRES

Product group	Tyres
Item number	15785511
Valid tyre size	23.5 R 25
LI / SI / PR	201 A2 / 185 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22



Bohnenkamp
Moving Professionals



Notes and features

- The BKT Earthmax SR 22 is an EM radial tyre for wheel loaders in winter use on snowy and icy surfaces
- The all-steel construction provides particular durability
- The block pattern with its large contact area provides good traction and stability

Technical Informations

Item number	15785511
EAN	8903094064342
Valid tyre size	23.5 R 25
LI / SI / PR	201 A2 / 185 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 22
TRA Code	E2/L2
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	307,07
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	6,50
Section width (mm)	610
Outer diameter of tyre [mm].	1614
Stat. radius (SLR) [mm]	709
Rolling circumference [mm].	4863
Tread depth (mm)	33,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
201 A2	14500	10		6,50	
185 B	9250	50		5,25	