

## TYRES

Product group	Tyres
Item number	15785520
Valid tyre size	650 / 65 R 25
LI / SI / PR	180 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 35



## Notes and features

- The BKT Earthmax SR 35 was specially developed for articulated dump trucks.
- Its special design enables very good traction and excellent flotation.
- The strong All Steel carcass and multiple steel belts provide excellent protection against cuts and punctures.
- The cut-resistant rubber compound (C.R.) ensures long tyre life even under difficult operating conditions.
- Additionally, the tyre is characterized by very good lateral stability.

## Technical Informations

Item number	15785520
EAN	8903094058587
Valid tyre size	650 / 65 R 25
Alternative size 1	25/65R25
LI / SI / PR	180 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 35
TRA Code	E3
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	352,11
Recommended rim size	19.50/2.5
Maximum air pressure [bar].	4,75
Section width (mm)	635
Outer diameter of tyre [mm].	1498
Stat. radius (SLR) [mm]	669
Rolling circumference [mm].	4493
Tread depth (mm)	39,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 B	8000	50		4,75	