

TYRES

Product group	Tyres
Item number	15785531
Valid tyre size	26.5 R 25
LI / SI / PR	202 A2 / 193 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 31



Notes and features

- Earthmax SR 31 is a radial all steel tyre for use on earthmovers, dozers and articulated joint tippers
- The construction featuring multiple layers of steel belts provides for a unique degree of resistance and stability
- The non-directional tread pattern allows for first-rate traction and manoeuvrability even on muddy soil as well as high driving comfort
- The particularly cut and heat resistant running surface compound provides for a tyre with a long service life
- The reduced rolling resistance results in significant fuel savings

Technical Informations

Item number	15785531
EAN	8903094053735
Valid tyre size	26.5 R 25
LI / SI / PR	202 A2 / 193 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 31
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	465,39
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	5,25
Section width (mm)	689
Outer diameter of tyre [mm].	1742
Stat. radius (SLR) [mm]	766
Rolling circumference [mm].	5200
Tread depth (mm)	38,0
Tyre capacity 75% [ltr.]	637.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
202 A2	15000	10	Loader dozer	5,00	
193 B	11500	50	Transport	5,25	