

TYRES

Product group	Tyres
Item number	15785536
Valid tyre size	26.5 R 25
LI / SI / PR	202 A2 / 193 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41



Notes and features

- The improved tread design provides maximum traction.
- All steel carcass with reinforced steel belt ply provides excellent stability and puncture resistance.
- The special tread compound (C.R. = Cut Resistance) offers best cut resistance in combination with excellent mileage and wear properties.
- Especially suitable for use on wheel loaders and dumpers.
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	15785536
EAN	8903094041206
Valid tyre size	26.5 R 25
LI / SI / PR	202 A2 / 193 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41
TRA Code	E4/L4
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	520,72
Recommended rim size	22.00/3.0
Permitted rim size	22.00/3.0IF
Maximum air pressure [bar].	4,50
Section width (mm)	678
Outer diameter of tyre [mm].	1742
Stat. radius (SLR) [mm]	775
Rolling circumference [mm].	5150
Tread depth (mm)	59,0
Tyre capacity 75% [litr.]	637.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
202 A2	15000	10	Loader dozer	4,50	
193 B	11500	50	Transport	4,50	