

TYRES

Product group	Tyres
Item number	15785541
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 50



Notes and features

- The directional, extra deep L-5 tread pattern with its lug geometry ensures a longer service life plus excellent traction and ride comfort
- The specially developed cut resistant running surface compound (C.R.= Cut Resistance) and the reinforced casing with multi-layer steel belts minimise cut and impact damage even under the toughest of conditions
- All-steel radial tyre, ideal for use on wheel loaders and bulldozers
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	15785541
EAN	8903094037070
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 50
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	670,99
Recommended rim size	22.00/3.0
Permitted rim size	22.00/3.0IF
Maximum air pressure [bar].	6,50
Section width (mm)	690
Outer diameter of tyre [mm].	1772
Stat. radius (SLR) [mm]	806
Rolling circumference [mm].	5334
Tread depth (mm)	89,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	558.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10		6,50	