

TYRES

Product group	Tyres
Item number	15785545
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 55



Notes and features

- The BKT Earthmax SR 55 was specially developed for loaders in mining and recycling applications
- Due to its very good cut resistance and the extra deep L5 tread pattern, the tyre is extremely puncture-proof and durable
- The high lateral stability provides high ride comfort

Technical Informations

Item number	15785545
EAN	8903094042128
Valid tyre size	26.5 R 25
LI / SI / PR	209 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 55
TRA Code	L5S
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	794,77
Recommended rim size	22.00/3.0
Maximum air pressure [bar].	6,50
Section width (mm)	690
Outer diameter of tyre [mm].	1786
Stat. radius (SLR) [mm]	810
Rolling circumference [mm].	5375
Tread depth (mm)	95,0
Tyre capacity 75% [ltr.]	558.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 A2	18500	10		6,50	