

## TYRES

Product group	Tyres
Item number	15785559
Valid tyre size	750 / 65 R 25
LI / SI / PR	202 A2 / 190 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 412



## Notes and features

- The BKT Earthmax SR 412 is an EM radial tyre for use on articulated dump trucks, on loaders and bulldozers
- The deep E4 tread pattern provides high traction and cut resistance
- Thanks to the strong, all-steel casing and steel belt design, the tyre provides high loading capacities, excellent stability and durability
- The squared shoulder design guarantees maximum ground contact for outstanding maneuverability

## Technical Informations

Item number	15785559
EAN	8903094065233
Valid tyre size	750 / 65 R 25
Alternative size 1	30/65R25
LI / SI / PR	202 A2 / 190 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 412
TRA Code	E4/L4
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	477,22
Recommended rim size	24.00/3.0
Permitted rim size	22.00/3.0, 25.00/3.0
Maximum air pressure [bar].	4,75
Section width (mm)	780
Outer diameter of tyre [mm].	1602
Stat. radius (SLR) [mm]	715
Rolling circumference [mm].	4838
Tread depth (mm)	55,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
202 A2	15000	10	Loader dozer	4,75	
190 B	10600	50	Transport	4,75	