

TYRES

Product group	Tyres
Item number	15785563
Valid tyre size	29.5 R 25
LI / SI / PR	208 A2 / 200 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41



Notes and features

- The improved tread design provides maximum traction.
- All steel carcass with reinforced steel belt ply provides excellent stability and puncture resistance.
- The special tread compound (C.R. = Cut Resistance) offers best cut resistance in combination with excellent mileage and wear properties.
- Especially suitable for use on wheel loaders and dumpers.
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	15785563
EAN	8903094039852
Valid tyre size	29.5 R 25
Alternative size 1	765/80R25
LI / SI / PR	208 A2 / 200 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 41
TRA Code	E4/L4
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	652,64
Recommended rim size	25.00/3.5
Maximum air pressure [bar].	4,50
Section width (mm)	761
Outer diameter of tyre [mm].	1861
Stat. radius (SLR) [mm]	830
Rolling circumference [mm].	5510
Tread depth (mm)	66,0
Tyre capacity 75% [litr.]	862.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
208 A2	18000	10	Loader dozer	4,50	
200 B	14000	50	Transport	4,50	