

TYRES

Product group	Tyres
Item number	15785570
Valid tyre size	29.5 R 25
LI / SI / PR	208 A2 / 200 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 30



Notes and features

- Full steel casing with extra steel belt layers for outstanding stability and puncture resistance
- Non-directional tread pattern for excellent traction properties
- The running surface's special rubber compound provides for optimum protection from cutting and impact damage as well as from heat development in the tyre during transport journeys
- Ideal for earthmovers, tippers and graders
- Suitable for mounting on one-piece rim

Technical Informations

Item number	15785570
EAN	8903094034291
Valid tyre size	29.5 R 25
Alternative size 1	765/80R25
LI / SI / PR	208 A2 / 200 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 30
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	618,99
Recommended rim size	25.00/3.5
Permitted rim size	25.00/3.5IF
Maximum air pressure [bar].	5,25
Section width (mm)	765
Outer diameter of tyre [mm].	1861
Stat. radius (SLR) [mm]	818
Rolling circumference [mm].	5555
Tread depth (mm)	42,0
Tyre capacity 75% [ltr.]	862.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
208 A2	18000	10	Loader dozer	5,25	
200 B	14000	50	Transport	5,25	