

TYRES

Product group	Tyres
Item number	15785571
Valid tyre size	29.5 R 25
LI / SI / PR	216 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 49 M



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 49 M is an all-steel radial tyre for loaders and dozers in stony terrain, especially in mining.
- The non-directional tread pattern offers very good traction and stability.
- The large tread depth (L4) and the special rubber compound ensure high wear resistance and good protection against tyre damage.

Technical Informations

Item number	15785571
EAN	8903094058440
Valid tyre size	29.5 R 25
LI / SI / PR	216 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 49 M
TRA Code	L4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	697,82
Recommended rim size	25.00/3.5
Permitted rim size	25.00/3.51F
Maximum air pressure [bar].	6,50
Section width (mm)	780
Outer diameter of tyre [mm].	1905
Stat. radius (SLR) [mm]	844
Rolling circumference [mm].	5600
Tread depth (mm)	57,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
216 A2	22400	10		6,50	