

TYRES

Product group	Tyres
Item number	15785572
Valid tyre size	750 / 65 R 25
LI / SI / PR	202 A2 / 190 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 35



Notes and features

- The BKT Earthmax SR 35 was specially developed for articulated dump trucks.
- Its special design enables very good traction and excellent flotation.
- The strong All Steel carcass and multiple steel belts provide excellent protection against cuts and punctures.
- The cut-resistant rubber compound (C.R.) ensures long tyre life even under difficult operating conditions.
- Additionally, the tyre is characterized by very good lateral stability.

Technical Informations

Item number	15785572
EAN	8903094051786
Valid tyre size	750 / 65 R 25
Alternative size 1	30/65R25
LI / SI / PR	202 A2 / 190 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 35
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	437,28
Recommended rim size	24.00/3.0
Permitted rim size	22.00/3.0, 25.00/3.0
Maximum air pressure [bar].	4,75
Section width (mm)	740
Outer diameter of tyre [mm].	1601
Stat. radius (SLR) [mm]	715
Rolling circumference [mm].	4802
Tread depth (mm)	42,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
202 A2	15000	10	Loader dozer	4,75	
190 B	10600	50	Transport	4,75	