

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15785572       |
| Valid tyre size | 750 / 65 R 25  |
| LI / SI / PR    | 190 B / 202 A2 |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Earthmax SR 35 |



## Notes and features

- The BKT Earthmax SR 35 was specially developed for articulated dump trucks.
- Its special design enables very good traction and excellent flotation.
- The strong All Steel carcass and multiple steel belts provide excellent protection against cuts and punctures.
- The cut-resistant rubber compound (C.R.) ensures long tyre life even under difficult operating conditions.
- Additionally, the tyre is characterized by very good lateral stability.

**Technical Informations**

|                              |                      |
|------------------------------|----------------------|
| Item number                  | 15785572             |
| EAN                          | 8903094051786        |
| Valid tyre size              | 750 / 65 R 25        |
| Alternative size 1           | 30/65R25             |
| LI / SI / PR                 | 190 B / 202 A2       |
| TL/TT                        | TL                   |
| Brand                        | BKT                  |
| Tread pattern                | Earthmax SR 35       |
| TRA Code                     | E3/L3                |
| Star Rating                  | **/*                 |
| Carcass properties           | C.R.                 |
| Antistatic                   | No                   |
| Tyre colour                  | Black                |
| ECE regulation number        | not necessary        |
| Nettogewicht [kg] (gültig)   | 437,28               |
| Recommended rim size         | 24.00/3.0            |
| Permitted rim size           | 22.00/3.0, 25.00/3.0 |
| Maximum air pressure [bar].  | 4,25                 |
| Section width (mm)           | 740                  |
| Outer diameter of tyre [mm]. | 1601                 |
| Stat. radius (SLR) [mm]      | 715                  |
| Rolling circumference [mm].  | 4802                 |
| Tread depth (mm)             | 42,0                 |
| E-Ready                      | No                   |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 190 B  | 10600              | 50           |               | 4,21                     |              |
| 202 A2 | 15000              | 10           |               | 4,75                     |              |