

TYRES

Product group	Tyres
Item number	15785573
Valid tyre size	775 / 65 R 29
LI / SI / PR	195 B / 206 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 35



Notes and features

- The BKT Earthmax SR 35 was specially developed for articulated dump trucks.
- Its special design enables very good traction and excellent flotation.
- The strong All Steel carcass and multiple steel belts provide excellent protection against cuts and punctures.
- The cut-resistant rubber compound (C.R.) ensures long tyre life even under difficult operating conditions.
- Additionally, the tyre is characterized by very good lateral stability.

Technical Informations

Item number	15785573
EAN	8903094064410
Valid tyre size	775 / 65 R 29
LI / SI / PR	195 B / 206 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 35
TRA Code	E3/L3
Star Rating	**/*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	562,14
Recommended rim size	24.00/3.5
Permitted rim size	24.00/3.0, 25.00/3.5
Maximum air pressure [bar].	4,75
Section width (mm)	775
Outer diameter of tyre [mm].	1752
Stat. radius (SLR) [mm]	787
Rolling circumference [mm].	5311
Tread depth (mm)	45,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
195 B	12150	50		4,75	
206 A2	17000	10		4,75	