

TYRES

Product group	Tyres
Item number	15785574
Valid tyre size	29.5 R 29
LI / SI / PR	223 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 49 M



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 49 M is an all-steel radial tyre for loaders and dozers in stony terrain, especially in mining.
- The non-directional tread pattern offers very good traction and stability.
- The large tread depth (L4) and the special rubber compound ensure high wear resistance and good protection against tyre damage.

Technical Informations

Item number	15785574
EAN	8903094052400
Valid tyre size	29.5 R 29
LI / SI / PR	223 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 49 M
TRA Code	L4
Star Rating	***
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	853,07
Recommended rim size	25.00/3.5
Permitted rim size	24.00/3.5, 26.00/3.5
Maximum air pressure [bar].	8,00
Section width (mm)	786
Outer diameter of tyre [mm].	2006
Stat. radius (SLR) [mm]	906
Rolling circumference [mm].	6320
Tread depth (mm)	60,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
223 A2	27250	10		8,00	