

## TYRES

Product group	Tyres
Item number	15785575
Valid tyre size	29.5 R 25
LI / SI / PR	208 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 50



## Notes and features

- The directional, extra deep L-5 tread pattern with its lug geometry ensures a longer service life plus excellent traction and ride comfort
- The specially developed cut resistant running surface compound (C.R.= Cut Resistance) and the reinforced casing with multi-layer steel belts minimise cut and impact damage even under the toughest of conditions
- All-steel radial tyre, ideal for use on wheel loaders and bulldozers
- Important: Mounting only permitted on multi-part rim.

## Technical Informations

Item number	15785575
EAN	8903094037230
Valid tyre size	29.5 R 25
LI / SI / PR	208 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 50
TRA Code	L5
Star Rating	*
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	842,66
Recommended rim size	25.00/3.5
Permitted rim size	25.00/3.51F
Maximum air pressure [bar].	5,00
Section width (mm)	775
Outer diameter of tyre [mm].	1901
Stat. radius (SLR) [mm]	862
Rolling circumference [mm].	5722
Tread depth (mm)	96,0
Number of lugs	23x2
Tyre capacity 75% [ltr.]	780
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
208 A2	18000	10		5,00	