

TYRES

Product group	Tyres
Item number	15785577
Valid tyre size	18.00 R 33
LI / SI / PR	191 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 47



Notes and features

- Steel casing for highest resistance against impact damage, breakage and puncture
- C.R. - Cut Resistance Rubber Compound
- Excellent traction on difficult terrain such as hard, rocks surfaces
- Especially suited for the front axle of tippers
- High tread pattern percentage for optimal steering characteristics
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	15785577
EAN	8903094045815
Valid tyre size	18.00 R 33
LI / SI / PR	191 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 47
TRA Code	E4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	517,93
Recommended rim size	13.00/2.5
Maximum air pressure [bar].	7,00
Section width (mm)	510
Outer diameter of tyre [mm].	1885
Stat. radius (SLR) [mm]	867
Rolling circumference [mm].	5674
Tread depth (mm)	64,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
191 B	10900	50		7,00	