Bohnenkamp Moving Professionals

TYRES

| Product group | Tyres | |
|-----------------|----------------|--|
| Item number | 15785578 | |
| Valid tyre size | 18.00 R 33 | |
| LI / SI / PR | 191 B | |
| TL/TT | TL | |
| Brand | ВКТ | |
| Tread pattern | Earthmax SR 45 | |



Notes and features

- Multi-layer steel belt for efficient protection from puncture damage
- Deep tread pattern for very good traction

- The extra-rugged casing and a special, cut-resistant rubber compound guarantee a long service life
- Important: Mounting only permitted on multi-part rim.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

| Item number | 15785578 |
|------------------------------|----------------|
| EAN | 8903094041145 |
| Valid tyre size | 18.00 R 33 |
| LI / SI / PR | 191 B |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | Earthmax SR 45 |
| TRA Code | E4 |
| Star Rating | ** |
| Carcass properties | C.R. |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 468,33 |
| Recommended rim size | 13.00/2.5 |
| Maximum air pressure [bar]. | 7,00 |
| Section width (mm) | 505 |
| Outer diameter of tyre [mm]. | 1870 |
| Stat. radius (SLR) [mm] | 856 |
| Rolling circumference [mm]. | 5608 |
| Tread depth (mm) | 55,0 |
| Tyre capacity 75% [ltr.] | 459.75 |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 191 B | 10900 | 50 | | 7,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.