

TYRES

Product group	Tyres	
Item number	15785581	
Valid tyre size	24.00 R 35	
LI / SI / PR	209 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Earthmax SR 45 M	



Notes and features

- The BKT Earthmax SR 45 M was specially developed for use on rigid dump trucks and dumpers
- A multi-layered steel belt provides efficient protection from puncture damage
- The deep tread pattern allows for very good traction
- The extra-rugged carcass and a special cut-resistant rubber compound guarantee a long service life.
- The updated tread pattern provides for improved stability compared to SR 45, through a bigger road contact surface
- Important: Mounting only permitted on multi-part rim.



Technical Informations

Item number	15785581
EAN	8903094029907
Valid tyre size	24.00 R 35
LI / SI / PR	209 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Earthmax SR 45 M
TRA Code	E4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	827,39
Recommended rim size	17.00/3.5
Maximum air pressure [bar].	7,00
Section width (mm)	664
Outer diameter of tyre [mm].	2180
Stat. radius (SLR) [mm]	980
Rolling circumference [mm].	6538
Tread depth (mm)	70,0
Tyre capacity 75% [ltr.]	853.5
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

In	dex	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
20	09 B	18500	50		7,00	