

TYRES

Product group	Tyres
Item number	15785583
Valid tyre size	35 / 65 R 33
LI / SI / PR	224 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 49



Notes and features

- The BKT SR 49 L4 was specially developed for wheel loaders and bulldozers in moderate to severe conditions
- Thanks to its deep, directional L4 tread pattern and its special rubber compound, the tyre is very well protected against wear and punctures
- Its optimally angled lugs ensure excellent traction and prevent wheelspin
- The square shoulder design prevents the penetration of loose stones and thus protects the tyre's sidewalls and shoulder from damages
- Its strong, all-steel casing and multiple steel belts provide high stability and puncture resistance
- Thanks to its self-cleaning properties, the tyre is perfectly protected against stone penetration

Technical Informations

Item number	15785583
EAN	8903094045082
Valid tyre size	35 / 65 R 33
LI / SI / PR	224 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 49
TRA Code	L4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	975.29
Recommended rim size	28.00/3.5
Maximum air pressure [bar].	6,50
Section width (mm)	899
Outer diameter of tyre [mm].	2061
Stat. radius (SLR) [mm]	890
Rolling circumference [mm].	6125
Tread depth (mm)	59,0
Tyre capacity 75% [ltr.]	1117.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
224 A2	28000	10		6,50	