

TYRES

Product group	Tyres
Item number	15785585
Valid tyre size	24.00 R 35
LI / SI / PR	209 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 47



Notes and features

- Steel casing for highest resistance against impact damage, breakage and puncture
- C.R. - Cut Resistance Rubber Compound
- Excellent traction on difficult terrain such as hard, rocks surfaces
- Especially suited for the front axle of tippers
- High tread pattern percentage for optimal steering characteristics
- Important: Mounting only permitted on multi-part rim.

Technical Informations

Item number	15785585
EAN	8903094041244
Valid tyre size	24.00 R 35
LI / SI / PR	209 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 47
TRA Code	E4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	864,23
Recommended rim size	17.00/3.5
Maximum air pressure [bar].	7,00
Section width (mm)	670
Outer diameter of tyre [mm].	2181
Stat. radius (SLR) [mm]	983
Rolling circumference [mm].	6565
Tread depth (mm)	73,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
209 B	18500	50		7,00	