

TYRES

Product group	Tyres
Item number	15785587
Valid tyre size	18.00 R 33
LI / SI / PR	214 A5
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PM 90



Notes and features

- The BKT Portmax PM 90 was specially developed for container handling equipment like reach stackers.
- Its optimum contact area enables even weight distribution.
- Thanks to its strong casing and reinforced sidewalls, the tyre provides excellent stability in lift mode.
- The deep tread pattern with the wide, centre rib and the wear-resistant tread compound ensure the tyre's long service life.
- Its optimal lug angle with reinforced shoulders minimises tyre damage.
- The tyre is able to dissipate static charge from the vehicle.

Technical Informations

Item number	15785587
EAN	8903094057184
Valid tyre size	18.00 R 33
LI / SI / PR	214 A5
TL/TT	TL
Brand	BKT
Tread pattern	Portmax PM 90
Star Rating	***
Antistatic	Yes
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	525,71
Recommended rim size	13.00/2.5
Permitted rim size	13.00/2.51F
Maximum air pressure [bar].	10,00
Section width (mm)	485
Outer diameter of tyre [mm].	1845
Stat. radius (SLR) [mm]	857
Rolling circumference [mm].	5624
Tread depth (mm)	67,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
214 A5	21200	25		10,00	