Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15785592
Valid tyre size	27.00 R 49
LI / SI / PR	223 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Earthmax SR 45 Plus



Notes and features

- The BKT SR 45 Plus was developed for rigid dumpers
- The unique E-4 tread pattern enables excellent traction and a long service life
- Its strong, all-steel casing and several steel belts provide excellent protection against damages through puncturing, cuts and wear
- The robust shoulder blocks protect the tyre against damages
- Wide grooves on the tread pattern and the tyre shoulder ensure very good self-cleaning properties
- The SR 45 Plus is available in standard, cut-resistant and heat-resistant versions

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15785592
EAN	8903094049806
Valid tyre size	27.00 R 49
LI / SI / PR	223 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Earthmax SR 45 Plus
TRA Code	E4
Star Rating	**
Carcass properties	STD
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	1.418,10
Recommended rim size	19.50/4.0
Maximum air pressure [bar].	7,00
Section width (mm)	746
Outer diameter of tyre [mm].	2702
Stat. radius (SLR) [mm]	1214
Rolling circumference [mm].	8095
Tread depth (mm)	73,0
Tyre capacity 75% [ltr.]	1410
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
223 B	27250	50		7,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.