

TYRES

Product group	Tyres
Item number	15785593
Valid tyre size	35 / 65 R 33
LI / SI / PR	224 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 51



Notes and features

- Reinforced, resistant all-steel carcass.
- Non-directional tyre, developed for wheel loaders and wheel dozers.
- Optimal lug angles for excellent traction in loading operations, grading work or moving larger quantities in the earthmoving sector.
- Extra deep tread (L5) combined with a robust and cut-resistant rubber compound guarantees a long service life.
- Developed for normal to extremely tough use.
- Self-cleaning tread pattern.
- Important: Assembly only permitted on multi-piece wheel.

Technical Informations

Item number	15785593
EAN	8903094066230
Valid tyre size	35 / 65 R 33
LI / SI / PR	224 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 51
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	1.046,60
Recommended rim size	28.00/3.5
Maximum air pressure [bar].	6,50
Section width (mm)	905
Outer diameter of tyre [mm].	2061
Stat. radius (SLR) [mm]	872
Rolling circumference [mm].	6082
Tread depth (mm)	95,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
224 A2	28000	10		6,50	