

TYRES

Product group	Tyres
Item number	15785594
Valid tyre size	45 / 65 R 39
LI / SI / PR	242 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 53



Notes and features

- Hardwearing L5 tread pattern design developed for wheel loaders and wheeled bulldozers
- Excellent suitability e.g. in quarries or in the mining industry for face-working operations and work on stony, very rough ground.
- The closed tread pattern design and the high tread pattern ratio (250%) make the SR53 the best choice for use in recycling e.g. scrap yards.
- Extremely robust and cut resistant rubber compound with minor abrasion and a long service life
- Very good self-cleaning properties with stone ejection
- Important: Assembly only permitted on multi-piece wheel.

Technical Informations

Item number	15785594
EAN	8903094067305
Valid tyre size	45 / 65 R 39
LI / SI / PR	242 A2
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 53
TRA Code	L5
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	2.206,40
Recommended rim size	36.00/4.5
Permitted rim size	32.00/4.5
Maximum air pressure [bar].	6,50
Section width (mm)	1100
Outer diameter of tyre [mm].	2577
Rolling circumference [mm].	7747
Tread depth (mm)	110,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
242 A2	47500	10	Loader dozer	6,50	