

## TYRES

Product group	Tyres
Item number	15785595
Valid tyre size	27.00 R 49
LI / SI / PR	223 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 46



## Notes and features

- The BKT SR 46 was developed for rigid mining dump trucks used in rocky, abrasive and harsh conditions
- The tread pattern with lug blocks and a circumferential groove enables perfect cornering with minimum tread face damage
- A large contact area with rigid blocks ensures even wear and a long service life
- The robust shoulder blocks prevent the penetration of smaller stones, thus protecting the sidewall from damages
- Its strong, all-steel casing and steel belts provide excellent protection against punctures, cuts or wear
- The SR 46 is available in standard and cut-resistant versions
- Attention: only approved for mounting on multi-part rim

## Technical Informations

Item number	15785595
EAN	8903094050161
Valid tyre size	27.00 R 49
LI / SI / PR	223 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 46
TRA Code	E4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	1.429,60
Recommended rim size	19.50/4.0
Maximum air pressure [bar].	7,00
Section width (mm)	746
Outer diameter of tyre [mm].	2688
Stat. radius (SLR) [mm]	1225
Rolling circumference [mm].	8165
Tread depth (mm)	68,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
223 B	27250	50		7,00	