

## **TYRES**

Product group	Tyres
Item number	15785599
Valid tyre size	24.00 R 35
LI / SI / PR	212 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 47



## Notes and features

- Steel casing for highest resistance against impact damage, breakage and puncture
- C.R. Cut Resistance Rubber Compound
- Excellent traction on difficult terrain such as hard, rocks surfaces
- Especially suited for the front axle of tippers
- High tread pattern percentage for optimal steering characteristics
- Important: Mounting only permitted on multi-part rim.



## **Technical Informations**

Item number	15785599
EAN	8903094060917
Valid tyre size	24.00 R 35
LI / SI / PR	212 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 47
TRA Code	E4
Star Rating	***
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	907,64
Recommended rim size	17.00/3.5
Maximum air pressure [bar].	8,00
Section width (mm)	670
Outer diameter of tyre [mm].	2181
Rolling circumference [mm].	6565
Tread depth (mm)	73,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
212 B	20000	50		8,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.