

## TYRES

Product group	Tyres
Item number	15785600
Valid tyre size	27.00 R 49
LI / SI / PR	223 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 48



## Notes and features

- The BKT Earthmax SR48 is an all-steel radial tyre for dump trucks
- It was specially developed for vehicles which have to transport heavy loads at higher speeds
- The tyre provides good grip and wear resistance in applications on rocky underground
- Its tread pattern and rubber compound offer high cut-resistance, even on particularly rocky underground
- The strong, all-steel casing and reinforced steel belts provide protection against puncturing and fatigue
- They prevent tyre damage caused by stone penetration
- The special shoulder design pushes loose stones aside and protects the sidewalls from cuts and other damages
- Attention: only approved for mounting on multi-part rim

## Technical Informations

Item number	15785600
EAN	8903094053209
Valid tyre size	27.00 R 49
LI / SI / PR	223 B
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 48
TRA Code	E4
Star Rating	**
Carcass properties	C.R.
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	1.429,60
Recommended rim size	19.50/4.0
Maximum air pressure [bar].	7,00
Section width (mm)	738
Outer diameter of tyre [mm].	2688
Stat. radius (SLR) [mm]	1225
Rolling circumference [mm].	8165
Tread depth (mm)	68,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
223 B	27250	50		7,00	