

TYRES

Product group	Tyres
Item number	17412110
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	165 A8, 20 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Excavator



Notes and features

- The Nokian Excavator is a special tyre for use on excavators.
- Its open tractor pattern with angled lugs and a reinforced tread centre provides excellent grip on wet and muddy soil.
- Thanks to the steel reinforcement and strong tyre shoulder, the tyre is perfectly protected against damages caused by stones or tree stumps.
- The tyre offers high loading capacities with low surface pressure and is therefore particularly suitable for parks and green areas.
- On the road, it impresses through its low vibration with very pleasant driving behaviour.

Technical Informations

Item number	17412110
EAN	6419440248332
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	165 A8, 20 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Excavator
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	141,93
Recommended rim size	20.00
Maximum air pressure [bar].	4,50
Section width (mm)	600
Outer diameter of tyre [mm].	1150
Stat. radius (SLR) [mm]	524
Rolling circumference [mm].	3506
Tread depth (mm)	40,0
Tyre capacity 75% [ltr.]	203
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 A8	5150	40		4,50	