

TYRES

Product group	Tyres	
Item number	17412112	
Valid tyre size	600 / 50 - 22.5	
LI / SI / PR	173 A8, 24 PR	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Excavator	



Notes and features

- The Nokian Excavator is a special tyre for use on excavators.
- Its open tractor pattern with angled lugs and a reinforced tread centre provides excellent grip on wet and muddy soil.
- Thanks to the steel reinforcement and strong tyre shoulder, the tyre is perfectly protected against damages caused by stones or tree stumps.
- The tyre offers high loading capacities with low surface pressure and is therefore particularly suitable for parks and green areas.
- On the road, it impresses through its low vibration with very pleasant driving behaviour.



Technical Informations

Item number	17412112
EAN	6419440218274
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	173 A8, 24 PR
TL/TT	TL
Brand	Nokian
Tread pattern	Excavator
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	141,48
Recommended rim size	20.00
Maximum air pressure [bar].	6,00
Section width (mm)	600
Outer diameter of tyre [mm].	1150
Stat. radius (SLR) [mm]	523
Rolling circumference [mm].	3531
Tread depth (mm)	40,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A8	6500	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.