

TYRES

Product group	Tyres
Item number	17415026
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	156 A2 / 149 A8, 16 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Nordman Forest TRS L-2



Notes and features

- Rugged bias casing.
- High load capacity and wear resistance.
- Excellent lateral grip thanks to the lug angle and pointed shoulder.
- Rugged, wide and high lugs.
- Suitable for CTL (Cut to length) machines and skidders or tractors in forestry use.

Technical Informations

Item number	17415026
EAN	6419440228716
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	156 A2 / 149 A8, 16 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Nordman Forest TRS L-2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	129,55
Recommended rim size	20.00
Maximum air pressure [bar].	3,20
Section width (mm)	600
Outer diameter of tyre [mm].	1171
Stat. radius (SLR) [mm]	545
Dynamic radius [mm]	564
Rolling circumference [mm].	3544
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 A2	4000	10		3,20	
149 A8	3250	40		3,20	