

TYRES

Product group	Tyres	
Item number	17415028	
Valid tyre size	710 / 40 - 22.5	
LI / SI / PR	158 A2 / 151 A8, 16 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	Nordman Forest F	



Notes and features

- Rugged bias casing.
- High load capacity and wear resistance.
- Excellent lateral grip thanks to the lug angle and pointed shoulder.
- Rugged, wide and high lugs.
- Ideally-suited for use with caterpillar tracks and chains.
- Optimum cut and puncture resistance.



Technical Informations

Item number	17415028
EAN	6419440228747
Valid tyre size	710 / 40 - 22.5
LI / SI / PR	158 A2 / 151 A8, 16 PR
TL/TT	тт
Brand	Nokian
Tread pattern	Nordman Forest F
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	136,34
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	710
Outer diameter of tyre [mm].	1171
Stat. radius (SLR) [mm]	538
Dynamic radius [mm]	564
Rolling circumference [mm].	3544
Tread depth (mm)	28,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 A2	4250	10		4,00	
151 A8	3450	40		4,00	