

TYRES

Product group	Tyres	
Item number	17415030	
Valid tyre size	600 / 55 - 26.5	
LI / SI / PR	172 A2 / 165 A8, 20 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	Nordman Forest TRS L-2	



Notes and features

- Rugged bias casing.
- High load capacity and wear resistance.
- Excellent lateral grip thanks to the lug angle and pointed shoulder.
- Rugged, wide and high lugs.
- Suitable for CTL (Cut to length) machines and skidders or tractors in forestry use.



Technical Informations

Item number	17415030
EAN	6419440455273
Valid tyre size	600 / 55 - 26.5
LI / SI / PR	172 A2 / 165 A8, 20 PR
TL/TT	тт
Brand	Nokian
Tread pattern	Nordman Forest TRS L-2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	189,00
Recommended rim size	20.00
Maximum air pressure [bar].	5,00
Section width (mm)	600
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	616
Dynamic radius [mm]	647
Rolling circumference [mm].	4065
Tyre capacity 75% [ltr.]	386
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A2	6300	10		5,00	
165 A8	5150	40		5,00	