

TYRES

Product group	Tyres	
Item number	17415032	
Valid tyre size	710 / 45 - 26.5	
LI / SI / PR	175 A2 / 168 A8, 20 PR	
TL/TT	тт	
Brand	Nokian	
Tread pattern	Nordman Forest TRS L-2	





Notes and features

- Rugged bias casing.
- High load capacity and wear resistance.
- Excellent lateral grip thanks to the lug angle and pointed shoulder.
- Rugged, wide and high lugs.
- Suitable for CTL (Cut to length) machines and skidders or tractors in forestry use.



Technical Informations

Item number	17415032
EAN	6419440455419
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TT
Brand	Nokian
Tread pattern	Nordman Forest TRS L-2
TRA Code	LS-2
Carcass properties	SF
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	213,30
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	608
Dynamic radius [mm]	649
Rolling circumference [mm].	4077
Tyre capacity 75% [ltr.]	490
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		5,00	
168 A8	5600	40		5,00	