Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	17415600	
Valid tyre size	710 / 50 R 26.5	
LI / SI / PR	170 D	
TL/TT	TL	
Brand	Nokian	
Tread pattern	Country King	



Notes and features

- Multifunctional tyre for agricultural trailers and vehicles.
- Approved for speeds up to 65 km/h.
- Very high payload.
- Excellent on-road and off-road ride comfort.
- Self-cleaning tread pattern reduces traces of soil on the road.
- Steel belted for high mileage and durability.
- Low rolling resistance reduces fuel costs.

05.02.2025

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	17415600
EAN	6419440454061
Valid tyre size	710 / 50 R 26.5
LI / SI / PR	170 D
TL/TT	TL
Brand	Nokian
Tread pattern	Country King
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	160,30
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	740
Outer diameter of tyre [mm].	1405
Stat. radius (SLR) [mm]	646
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4304
Tread depth (mm)	20,0
Tyre capacity 75% [ltr.]	655
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		4,00	
	7440	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.