

TYRES

Product group	Tyres
Item number	17415700
Valid tyre size	650 / 55 R 26.5
LI / SI / PR	177 D
TL/TT	TL
Brand	Nokian
Tread pattern	CT



Notes and features

- The tyre's wide contact area enables good lateral stability when unloading and high flotation on soft surfaces.
- The arrangement of the blocks with wide, angled spaces ensures good self-cleaning.
- Its special wear-resistant rubber compound was developed for operations on challenging ground such as rocky surfaces, as well as for road use.
- High-strength steel belt reinforcements combined with a cut- and crack-resistant rubber compound provide high puncture protection.
- The special construction of several steel plies allows high inflation pressures and increases the stability of the tyre.
- The asymmetrical arrangement of the blocks, which successively come into contact with the ground surface, reduces the noise generated when driving on the road.

Technical Informations

Item number	17415700
EAN	6419440455563
Valid tyre size	650 / 55 R 26.5
LI / SI / PR	177 D
TL/TT	TL
Brand	Nokian
Tread pattern	CT
Carcass properties	HD,Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	218,44
Recommended rim size	20.00
Permitted rim size	22.00
Maximum air pressure [bar].	6,00
Section width (mm)	645
Outer diameter of tyre [mm].	1389
Stat. radius (SLR) [mm]	639
Rolling circumference [mm].	4247
Tread depth (mm)	27,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 D	7300	65		6,00	