

TYRES

Product group	Tyres
Item number	17415810
Valid tyre size	800 / 50 R 34
LI / SI / PR	181 D
TL/TT	TL
Brand	Nokian
Tread pattern	ELS



Notes and features

- The flotation radial tyre was specially designed for field applications, if field use clearly predominates over road use.
- Thanks to its high load capacity, it is especially suitable for heavy agricultural machines and trailers.
- In the SB versions, the tyre is extremely robust due to the steel belt.
- Particularly gentle on the soil due to its wide contact area, rounded shoulders and low tyre pressure. Also suitable for delicate green areas.
- Very good grip and steering characteristics on soft surfaces.

Technical Informations

Item number	17415810
EAN	6419440454696
Valid tyre size	800 / 50 R 34
LI / SI / PR	181 D
TL/TT	TL
Brand	Nokian
Tread pattern	ELS
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	232,98
Recommended rim size	25
Permitted rim size	23, 24, 28
Maximum air pressure [bar].	4,00
Section width (mm)	800
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	801
Rolling circumference [mm].	5089
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		4,00	