

## TYRES

Product group	Tyres
Item number	17415895
Valid tyre size	600 / 55 R 26.5
LI / SI / PR	173 D
TL/TT	TL
Brand	Nokian
Tread pattern	CT



## Notes and features

- The tyre's wide contact area enables good lateral stability when unloading and high flotation on soft surfaces.
- The arrangement of the blocks with wide, angled spaces ensures good self-cleaning.
- Its special wear-resistant rubber compound was developed for operations on challenging ground such as rocky surfaces, as well as for road use.
- High-strength steel belt reinforcements combined with a cut- and crack-resistant rubber compound provide high puncture protection.
- The special construction of several steel plies allows high inflation pressures and increases the stability of the tyre.
- The asymmetrical arrangement of the blocks, which successively come into contact with the ground surface, reduces the noise generated when driving on the road.

## Technical Informations

Item number	17415895
EAN	6419440473062
Valid tyre size	600 / 55 R 26.5
LI / SI / PR	173 D
TL/TT	TL
Brand	Nokian
Tread pattern	CT
Carcass properties	HD,Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	177,98
Recommended rim size	AG20.00H2
Maximum air pressure [bar].	6,00
Section width (mm)	610
Outer diameter of tyre [mm].	1335
Stat. radius (SLR) [mm]	612
Rolling circumference [mm].	4098
Tread depth (mm)	24,0
Tyre capacity 75% [ltr.]	355
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		6,00	